


Vulcan code 3168
rec 5-19-09

1-1-2-E

EXCEL POLYMERS LLC
MATERIAL SAFETY DATA SHEET



DESICAL P - GRID PAK

Version Number 1.3
Revision Date 12/11/2006

Page 1 of 6
Print Date 1/10/2007

I. PRODUCT AND COMPANY IDENTIFICATION

EXCEL POLYMERS LLC
14330 Kinsman Road, Burton, OH 44021

Telephone : Product Stewardship (440) 834-4644
Emergency telephone number : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name : DESICAL P - GRID PAK
Product code : AD0000060960
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	10 - 30
Calcium oxide	1305-78-8	60 - 100

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Calcium oxide reacts with water to produce enough heat to ignite combustible materials. This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure: : Inhalation, Skin contact, Ingestion

Acute exposure

Inhalation : Causes irritation and inflammation to mucous membrane and respiratory passages.
Ingestion : May be harmful if swallowed.
Eyes : Acute eye irritation/corrosion
Skin : Skin contact may cause redness, irritation, and burns.

Chronic exposure : Refer to Section 11 for Toxicological Information.

MARKETED BY
**HARWICK STANDARD
DISTRIBUTION CORPORATION**
60 S. Seiberling Street • Akron, Ohio 44305

EXCEL POLYMERS LLC
MATERIAL SAFETY DATA SHEET



DESICAL P - GRID PAK

Version Number 1.3
Revision Date 12/11/2006

Page 2 of 6
Print Date 1/10/2007

Medical Conditions : None known.
Aggravated by Exposure:

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : No data available

Flammable Limits
Upper explosion limit : No data available
Lower explosion limit : No data available
Autoignition temperature : Not applicable
Suitable extinguishing media : Carbon dioxide blanket, dry powder, foam.

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

Unusual Fire/Explosion Hazards : Calcium oxide reacts with water to produce enough heat to ignite combustible materials. Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil. Should not be released into the environment.

Methods for cleaning up : Pick up and transfer to properly labelled containers. Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

9. PHYSICAL AND CHEMICAL PROPERTIES